







3 cabins 3 heads - Skipper's cabin version:



General Equipment list - Europe

GENERAL SPECIFICATIONS_____

 L.O.A Hull length L.W.L. Beam Standard draft (T-keel) Standard ballast weight (Cast iron) Performance draft (T-keel) Performance ballast weight (Cast iron/ Lead) Air draft (excluding antennae) Performance air draught (excluding antennae) Light displacement Evel case site (standard) 	17,12m 15,98m 15,40m 2,50m 4 500kg 3,02m 4 510kg 25,88m 26,88m 15 599kg	56'2" 52'5" 50'6" 16'5" 8'2" 9,918 lbs 9'11" 9,940 lbs 85' 88' 34,380 lbs
Fuel capacity (standard)Fresh water capacity (standard)	400L 720L	106 US Gal 190 US Gal
 Engine power: Sail drive (standard) Propeller shaft (Option) 	80 HP 110 HP	80 HP 110 HP

ARCHITECTS / DESIGNERS _____

- Naval Architect: BISCONTINI YACHT DESIGN
- Outside & interior design: LORENZO ARGENTO

EC CERTIFICATION ____

- Category A 10 people
 Category B 12 people
 Category C 14 people

STANDARD SAILS DIMENSIONS _____

ALUMINUM MAST WITH IN-BUILT FURLER

• Mainsail	87,50m²	942 sq/ft
 Furling genoa (105 %) 	73,36m²	790 sq/ft
Code 0	162m²	1,744 sq/ft
 Asymmetric spinnaker 	254,00m ²	2,730 sq/ft
•	21,95m	72'
ل •	6,40m	21'
• P	22,00m	72'2''
• E	6,80m	22'4''

CARBON CLASSICAL MAST (+ 1m / 3'3")

 Performance version mainsail Furling genoa (105 %) Code 0 Asymmetric spinnaker I J P 	89,50m ² 76,90m ² 160m ² 265,00m ² 22,90m 6,40m 23,00m	963 sq/ft 828 sq/ft 1,722 sq/ft 2,850 sq/ft 75'2'' 21' 75'6''
• P	23,00m	75'6''
• E	6,80m	22'4"



CONNECT YOUR BOAT FREE YOUR MIND



General Equipment list - Europe

STANDARD EQUIPMENT

CONSTRUCTION

- · Design in accordance with European Directive requirements and according to CE certification
- ISO 12215 certified structure
- · Balsa sandwich infusion hull
- · Vacuum infused structural inner liner (Fabrics resin) bonded to the hull
- · Deck in glass fibre/balsa wood sandwich infusion, with non-slip "diamond point" surface
- · Cast iron keel attached with bolts and bonded stainless steel backplate
- · Twin rudders hung with stainless steel stock
- White coloured hull Aluminum grey hull decoration
- · 8 Hull portholes

DECK EQUIPMENT

RIGGING

- · Depending on version:
- Black lacquered aluminum classical mast tapered, deck stepped.
- 3 Aft swept spreaders,
- C-strand Rigging,

C-strand backstay crowfoot with manual hydraulic piston to starboard (hydraulic unit optional),

Harken fixed blocks at foot of mast,

- Harken Switch mainsail track (without traveller)
- Performance carbon classical mast tapered, deck-stepped (+ 1m / 3'3", Weight saving: 100kg / 220 lbs)

3 Aft swept spreaders

ROD Rigging

Textile backstay crow's foot with manual hydraulic piston to starboard

- Harken fixed blocks at foot of mast
- Harken Switch mainsail track (without traveller)
- Black lacquered aluminium Racing boom with LED lighting (warm white)
- Black Racing lacquered aluminum rigid kicking strap with Dyneema tackle and friction rings (hydraulic available as an option)
- Genoa track on the roof with traveller and hauling line controlled from the cockpit
- Manual Genoa furler below deck
- 1 mainsail attachment point at bottom of cockpit with 1 stand-up block
- · German system (Two-way mainsheet at the helm station)
- · All lines brought back to the helm stations (except boom topping lift)
- Dyneema Complete running rigging:
- Mainsheet halyard sheave block,
- Genoa halyard,
- Boom uphaul (polyester) with cleat on mast,
- Mainsheet,
- 2 Genoa sheets,
- 2 Automatic reefing system
- 7 halyard clutches to port, 4 to starboard HARKEN Black Magic blocks
- · 2 Spinnaker sheet chain plates/code 0 Running rigging hidden
- · 2 Flag halyards

WINCHES

- 1 Manual self-tailing winch to starboard (H50.2 STP)
- 1 Electric self-tailing winch to port (H50.2 STPE)
- 2 Manual Genoa winches (H70.2 STP)
- 2 Aluminum Speed Grip winch handles
- · Stowage of which handles in dedicated space in rope bags

March 20, 2023 - (non-binding document)

SAILS

· Boast supplied without sail

MOORING LINES - MOORING

- · Polyester bowsprit with integrated anchoring gear and bobstay with spinnaker chainplate (for Code 0 and asymmetric spinnaker)
- · Self-draining chain locker, Clench bolt, Piston-driven cover
- Single roller stainless steel bow fitting
- 12 V 1 500 W vertical electrical windlass Remote control in mooring locker
- 6 Black anodised aluminum mooring cleats (Length: 0,40m / 1'4")
- · Stainless steel chafing plate

SAIL LOCKER

Access through T70 deck hatch, Passage width: 0,65 x 0,65m / 2'2" x 2'2'

- · Stainless steel ladder
- · Shelving and stowage trays
- LED lighting
- 1 230 V socket

SAFETY ON DECK

- · 1 Black lacquered stainless steel open pulpit
- · 2 Black lacquered stainless steel aft pulpits with integrated fairlead
- 1 Black lacquered stainless steel central aft pulpit (Height: 960mm / 3'2")
- · 2 Black lacquered stainless steel handrails on the roof
- · 1 Lifebuoy support bracket on aft pulpit
- Wooden flagstaff (1 m/3'3") with integrated support on deck
- · Dual textile lifelines and black lacquered stainless steel stanchions (Height: 620mm / 2') - Side boarding gate on either side
- · Emergency ladder on pushpit

COCKPIT

- · Self-draining cockpit
- Iroko slatted
- · 2 Sail lockers below cockpit seating
- · 2 Stowage lockers behind the cockpit with stainless steel support for the fenders (650 x 390mm / 2'2" x 1'3")
- 1 Access hatch to tender garage
- · 1 Integrated housing in catwalks for diesel deck filler and shore power socket
- 3 water deck fillers at the forward end of the roof on the catwalks
- 1 Gas locker on forward deck next to anchor chain locker, space of 2 bottles
- · Iroko slatted on companionway sunbeds
- Iroko slatted cockpit benches
- Iroko slatted side helmsman's seat
- · Foldaway helmsman foot chock
- · 2 Removable footrests at the rear of the helm station
- 2 Steering wheel consoles:
 - Black composite helm (diameter 1 100 mm/3'7') fixed on white lacquered aluminum pedestal
 - Steering gear at the helm station
 - Stainless steel steering chain transmission system
 - Black lacquered stainless steel hand rail
- 1 Emergency tiller
- 1 Steering compass on port console
- · Engine throttle and control panel on starboard

liferaft: 0,96m x 0,59m x 0,40m / 3'2" x 1'11" x 1'4")

• 1 Cockpit shower with mixer tap in the tender garage · 1 PPMA folding companionway door in the bottom of the cockpit -Sliding hatch made of PMMA

Code Bénéteau V12821 (B) Eng

· Liferaft locker in front of the companionway (Space for 12 place

• Courtesy lighting (7 LED lighting points, warm white lighting)



SWIM PLATFORM / AFT TRANSOM

- Fully opening transom, convertible to bathing platform (2,61m x 0,93m / 8'7" x 3'1")
- · 3 Folding access steps to the cockpit to starboard
- · Electrically controlled opening on console
- · Iroko slatted swim deck
- 1 Stainless steel, removable bathing ladder with dedicated stowage in the cockpit

TENDER GARAGE

Accessible from the platform and from the cockpit Can be used to house a Highfield UL240 type tender (2,48m x 1,69m x 0,80m / 8'2" x 5'7" x 2'7")

• 1 Touch-operated ceiling LEDs

INTERIOR

- Alpi teak woodwork and white lacquered wood on base units and bulkheads
- Alpikord teak flooring
- · Lounge Falcon 162 fabric interior upholstery
- Mattresses in the cabins (HR foam 35 kg/m3, thickness 120 mm/5")
- Beige padded ceilings (and Macadamia in the central part of the saloon)

Standard version: 3 cabins + 2 heads



COMPANIONWAY

Headroom: 2,00m / 6'7"

- Saloon companionway with 5 suspended Alpikord teak non-slip steps, LED lighting below each step
- · 2 Valencia Meteor encased stainless steel handrails

SALOON

Headroom: 2,00 - 1,97m / 6'7" / 6'6"

Starboard saloon:

- · Very comfortable Lounge type L-shaped sofa:
- seats with HR26 and HR30 foam
- softness thanks to the finish with hollow fibres + padding
- Coffee table, wooden top with moulded beading, access to bottle rack opposite the seat
- · Storage under bench seats
- 1 Electrical panel to starboard incorporated into a piece of furniture for access to electrical connections
- 2 Portholes with integrated blind
- 2 Coachroof windows including opening porthole with mosquito net
- · 2 Opening deck hatches with mosquito screen/blinds
- Indirect LED lighting below the soft and the upper part of the portholes
- 1 Adjustable reading light
- 1 dual USB port
- 1 230 V socket
- Audio:
- Fusion RA70N entertainment system
- 2 Interior loudspeakers
- 2 Waterproof exterior speakers

General Equipment list - Europe

Port saloon:

- Wooden table with integrated sliding extension leaf
- Face-to-face bench seats with extension (can seat up to 6 diners)
- 2 Portholes with integrated blind
- Storage under bench seats
- 1 Deep storage unit against bulkhead + 1 Valet tray (unless air conditioning option chosen)
- Indirect LED lighting on the upper part of the portholes
- 1 230 V socket close to forward bulkhead
- Pillar with beige cover

GALLEY - PORT

- Headroom: 2,01m / 6'7"
- C-shaped galley
- Corian Glacier White work top with moulded Apli teak beading
- 1 1 rectangular stainless steel sink 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 3 burners Stainless steel/grill fitted on swivel joints (19L) - Stainless steel protection handrail - Stowage below the oven with drop-down door - Tempered glass cover on the hotplate
- 1 Stowage on work top with top opening (Space for optional 36 L stainless steel cool box)
- 1 3 drawer storage on the work top (Space for the dishwasher option)
- 12 V 174 L fridge with integrated 16 L freezer (-18 °C), 1 Front opening door
- · Fitted lockers and closed shelving
- 1 Bin (20L)
- 1 Base unit: 1 drawer on the side, 2 doors, 1 shelf
- 2 Opening portholes with mosquito nets

OWNER'S CABIN

Headroom: 2,01 - 1,96m / 6'7" - 6'5"

- Central double bed (2,00m x 1,60m 1,15m / 6'9" x 5'3" 3'9") with Lounge Greige 160 fabric padded bedstead
- 1 Bed access sideboard
- 1 Chair on each side of bed with Lounge Falcon 162 fabric
- 2 Shoe stowage beneath the bed
- · 2 Hanger closets, with incorporated LED lighting
- 1 Central full-height unit with LED lighting: 4 drawers at the bottom, 1 door with 4 shelves, mirror inside the door
- 2 Night tables
- 2 Flexible and adjustable bedside lamps
- 1 T70 flush deck hatch with blind/mosquito net
- 2 Portholes with rigid sliding blind
- 1 230 V power socket on each side of the bed
- 1 dual USB port outlet on each side of the bed
- LED indirect lighting + Spot lighting
- 2 PRIVATE HEADS

To starboard:

- Headroom: 1,92m / 6'4"
- 1 Manual toilet
- 1 80 L / 13 US Gal rigid holding tank
- Work top in Corian Glacier White
- 1 Integrated polyester basin Mixer tap
- 1 Cabinet Mirror
- Toilet accessories
- 1 Deck hatch with mosquito screen/blind
- LED indirect lighting + Spot lighting

<u>to port:</u>

- Headroom: 1,97m / *6'*6"
- · Shower with seat and wooden shower base
- 2 Open stowage trays
- 1 Deck hatch with mosquito screen/blind
- LED indirect lighting



General Equipment list - Europe

PORT AFT CABIN

- Headroom: 1,92m / 6'4"
- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED lighting
- 2 Lockers with top opening along the hull
- 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- 1 Flexible and adjustable reading light on the hanging locker
- 1 dual USB port
- 1 230 V socket
- 1 Porthole with rigid sliding blind
- 1 Opening window with below cockpit seat with pleated blind
- 2 Opening windows on coaming with pleated blind (1 with the 3 heads version)

STARBOARD AFT CABIN

- Headroom: 1,92m / 6'4"
- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- 1 Hanging locker, 2 lockers with top opening along the hull
- 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- 1 Flexible and adjustable reading light on the hanging locker
- 1 USB socket
- 1 230 V socket
- 1 Porthole with rigid sliding blind
- · 2 Opening windows with below cockpit seat with pleated blind
- 1 Opening window on coaming with pleated blind

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,95m / 6'5"

Access from the saloon or the starboard aft cabin

- Separate shower 1 Mixer tap White polyester shower base
- · Corian Glacier White work top with self-draining storage
- 1 Manual toilet
- 1 80 L / 21 US Gal rigid holding tank
- 1 Washbasin 1 Mixer tap
- 1 Cabinet + Storage space under the basin
- 2 Mirrors
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen

3 cabins 3 heads version (Option)



This head stands between the galley and the after port cabin: single hanging locker and one opening porthole in the aft cabin

AFT PORT HEAD COMPARTMENT

Headroom: 2,03m / 6'8"

Access by the aft starboard cabin

- Polyester work top with integrated basin 1 Mixer tap 1 Shower -White polyester shower base
- 1 Quiet Flush fresh water/seawater electric WC
- 1 50 L / 13 US Gal rigid holding tank
- 1 Bathroom cabinet 2 doors
- 1 Mirror above the washbasin
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- 1 Fixed window on coaming, opaque film



General Equipment list - Europe

ENGINE

- Engine Yanmar Diesel:
 - 80 HP, Sail Drive, Common Rail (standard)
 - 110 HP, Propeller shaft, Common Rail (Option)
- · Engine control at the starboard helm station Control panel
- · Engine compartment:
 - Soundproofing foam
 - Ventilation: 2 air intakes and 1 forced air outlets
- Automatic LED lighting · Engine data visible on the B&G screen
- 1 Alternator (12V / 125Ah)
- 2 Rotomoulded diesel tanks 2 x 200L / 2 x 53 US Gal (under aft berth port and starboard) - Electronic gauge - Low level alarm -1 Deck filler
- · Filters: Seawater Diesel Water separator
- · Foldable three-blade propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- 2 Engine access through aft cabins

PLUMBING

- 1 Rotomoulded freshwater tank 380 L / 100 US Gal, under berth in forward cabin - 1 Deck filler
- 2 Rotomoulded freshwater tanks 2 x 150L / 2 x 40 US Gal, under saloon floor, port and starboard - 1 Deck filler
- · Pressurised electric water pump Expansion tank Inline filter
- 40 L / 11 US Gal Electric water heater (engine use)
- 1 Rigid black water holding tank for each WC
- · Electrical shower drain pumps
- 1 Electric bilge pump
- 1 Manual bilge pump
- Transfer valves easily accessible from the companionway

GAS

- 1 Box for 2 gas bottles in the anchor locker (Diameter: 0,28m / 11"x Height: 0,45m / 1'6")
- · Regulator and safety tap
- · Gas leak detector

SMART BOARD

"SEANAPPS" smart technology:

- · For monitoring the boat's status and receiving alerts as well as maintenance advice via the associated mobile application.
- The type of information collected (GPS position, batteries, engine info, navigation data, etc.) varies according to the boat's configuration.



ELECTRICITY

- 12 V electrical panel (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + dual USB port + Navicolor 3.5" screen
- Radio controlled wireless light switches (no battery) for lighting (excluding heads)
- 10 touchscreen table on the electrical panel, dedicated to Ship Control, allowing all functions to be managed from the saloon
- · Ship Control technology control numerous functions from the navigation screens (or from a tablet or smartphone using a dedicated app):
- Anchoring and masthead navigation lights
- Lighting of boom, spreaders (optional), underwater spotlights (optional)
- Courtesy light in cockpit
- Direct lighting
- Deck searchlight
- Inverter (Option)
- Fridge
- Water unit
- Bilge pumps
- Air conditioning (Option) - Generator (Option)
- Audio
- Control of levels (diesel, fresh water, black water)
- Battery monitoring
- 12V circuit
- 3 AGM service batteries (140Ah) 1 AGM engine battery (100Ah)
- · Battery cut-off switch easily accessible from the companionway
- 1 Battery charger (25Ah)
- 1 Battery charger (40Ah)
- 1 Power distributor
- 11 230V Sockets:
- 2 in the forward cabin
- 1 in the forward port head
- 1 in the aft cabins
- 1 in the saloon (Starboard)
- 1 at chart table
- 2 in galley
- 1 in the engine compartment
- 1 in the sail locker
- 6 Dual USB socket:
 - 2 in the forward cabin
 - 1 in the aft cabins
 - 1 on the electrical panel
 - 1 at chart table
- 1 Shore power socket 230 V
- LED lighting:
- Overhead lights, with dimmer - Reading lights
- Indirect lighting, with dimmer
- LED navigation lights:
 - 1 Masthead light - 1 Steaming light
- 1 Anchor light on masthead Deck searchlight (Halogen)
- · Wire runs for option cables

MISCELLANEOUS ITEMS

· Smoke detector



TRIM LEVEL & PACKS

TRIM LEVEL _____

	CONFORT	LUXE
Coastal Pack (GARMIN)		
1 Harken Performa H50.2 STPEH starboard electric manoeuvring winch (in lieu of standard)		
Windlass control in cockpit with chain counter		
Tilting transom remote control	•	
 Retractable bow thruster + 4 Dedicated batteries (50 Amps - 12V) + 1 Battery charger (30 Amps - 24V) 	-	•
TECMA electric fresh water/sea water WC in the owner's head		
IBS sensor		
2 Additional 140 ampères service batteries		
Electrical engine control on the starboard console		
Mosquito nets for opening portholes	•	
Offshore Pack (GARMIN)		
2 Solid wood cockpit tables with additional leaves (2 on the sides, 1 in the centre) on stainless steel pedestal and Charcoal Grey cover		
Outside cockpit upholstery, Sunbrella Terry beige seats and backrests (terrycloth), Filter foam 80 mm/3" thickness (Density: 60F + 20S)		
Spring mattress in the owner's cabin (thickness: 180mm / 7")		-
Quiet Flush fresh water/seawater electric WC in the aft starboard head		-

ELECTRONICS PACKS: GARMIN ______

	COASTAL (included in the Confort trim level)	OFFSHORE (included in the Luxe trim level)
 Port and starboard helm stations: 1 12" GPS Map 1223 multi-function touchscreen (GPS, Chart plotter, Card reader - Bluechart G3 cartography included) Wind Sensor gWind Race - pole 1m / 3'3": Windvane, Anenometer 	•	•
 Airmar DST810 Sensor (Log, Speedometer, Temperature) PC interface (GND10) 	•	-
 Fixed 315i VHF at chart table, without AIS receiver function Windex Windyane 		
 Protective covers for helm & consoles (Charcoal Grey) 		
 Reactor 40 Pilot with GHC 50 control on port console Wireless autopilot remote control GARMIN Quatix 7 connected watch 		

FASTNET PACK (implies pack Coastal or Offshore pack)

- 3 GNX120 7" mast screens + mast bracket + cover
- 800 AIS
 GHS11 VHF Wired handset at port helm station



General Equipment list - Europe

RIGGING PACKS

MAINSAIL WINCH PACK (Compatible with the 2 masts)

- Self-tailing HARKEN Performa (H50.2 STPEH) electric winch on polyester turret in centre of cockpit
- Standard German System replaced by 1 Dyneema mainsheet

DOWNWIND PACK (Compatible with the 2 masts)

- · 2 Additional halyard clutches to starboard
- 2 HARKEN Black Magic blocks for spinnaker/code 0 sheet
- 1 HARKEN Black Magic block for spinnaker tack led back to the dedicated cleat in the cockpit
- 1 Dyneema halyard sheave with block for spinnaker or code 0
- 1 Dyneema halyard for spinnaker
- · 1 Spinnaker tackline with return on dedicated cleat in cockpit
- · Barber hauler (Chain plate on bulwark)

STAYSAIL RIGGING PACK (Compatible with the 2 masts requires the self-tacking rigging pack)

- 1 Wichard double chainplate on forward deck for removable forestay
- · 1 Dyneema halyard sheave with block for staysail

SELF-TACKING RIGGING PACK (Compatible with all masts and all rigging packs - Requires the pack Downwind)

- Self-tacking jib hardware (sheet only)
- 1 Self-tacking jib track with traveller

CARBON MAST SAILS PACK

- Full batten mainsail (91 m²/979 sg/ft) and Genoa (82 m²/882 sg/ft) North Sails NPL tour, dark grey
- Charcoal Grey lazy bag + lazy jack

ALUMINUM SAILS MAST PACK

- Full batten mainsail (87 m²/936 sq/ft) and Genoa (82 m²/882 sq/ft) North Sails NPL tour, dark grey
- Charcoal Grey lazy bag + lazy jack

MOORING PACK

- Delta 32 kg/71 *lbs* anchor (galvanized steel)
 Chain (Diameter: 12mm / ¹/₂" Length: 40m / 131')
 Line (Diameter: 22mm / ⁷/₈" Length: 50m / 164')
- 6 Fenders:
- 4 XL (Diameter: 300mm / 12" Length: 880mm / 2'11")
- 2 L (Diameter: 250mm / 10" Length: 700mm / 2'4")
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3")

MOORING PACK (inflatable)

- Delta 32 kg/71 *lbs* anchor (galvanized steel)
 Chain (Diameter: 12mm / ¹/₂" Length: 40m / 131')
 Line (Diameter: 22mm / ⁷/₈" Length: 50m / 164')
- 6 Fenders (Diameter: 360mm / 1'2" Length: 1 200mm / 3'11")
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3")

OPTIONS

NAVIGATION ELECTRONICS: GARMIN

- Chart table: 12" GPS Map 1223 multi-function touchscreen
- 800 AIS · Panoptix PS51-TH (Forward underwater vision)
- Fantom 18x radar
- · GHS 11 VHF Wired handset at port helm station

RIGGING - SAILS

- FurlerBoom V-shaped boom furler, black lacquered, epoxy glassfibre casing/carbon spindle. Integrated LED lighting for the cockpit area. For aluminium or carbon mast. (Requires hydraulic unit option)
- · Hydraulic unit (for carbon mast): Hydraulic textile backstay on piston + Hydraulic kicker tackle on unit (2 Functions / 2 speeds)
- Hydraulic unit (for aluminum mast): ROD rigging and hydraulic textile backstay on piston + Hydraulic kicker tackle on unit (2 Functions / 2 speeds)
- Electric Genoa furler below deck
- Aluminum black lacquered canoe boom with hydraulic piston, Sparcraft (Requires hydraulic unit option), Integrated LED lighting for the cockpit area
- Code 0 with North Sails NPL tour furler, laminated, dark grey (for aluminum mast)
- · Code 0 with North Sails NPL tour furler, laminated, dark grey (for carbon mast)

WINCHES

• 2 Electric Harken Performa genoa sheet winches (H70.2 STPEH)



HULL - DECK - COCKPIT

- Pearl grey gel-coat (Hull & Bowsprit)
- Metallic hull paint (Hull Aft transom Bowsprit)
- Iroko slatted side decks
- Iroko slatted roof
- Retractable capstan (Bow)
- LED lighting of spreaders
- Retractable stern thruster
- Carbon or white composite helm
- Retractable NOMEN black anodised cleats (in lieu of standard)
- Accommodation ladder
- Outboard engine bracket
- Polyester folding gangway (2,60m / 8'6")
- Electric inflator/deflator for tender and fenders (portable, batterypowered)
- Shore fresh water supply
- Seawater/fresh water deck washing pump
- 3 Underwater lights (1 forward, 2 aft)
- 1,20 m/3'11" carbon flagstaff (in lieu of standard)
- Tender launching system (Manual winch, 1 roller)
- 32 kg/71 lbs stainless steel anchor upgrade for anchoring pack
- Unpainted stainless steel lifelines and stanchions

COCKPIT COMFORT

- Dolce 51 cockpit upholstery (requires Luxe trim level, as a replacement for the Terry beige upholstery)
- Electrical bases + mattress for the 2 cockpit tables (for the sun deck bed function) in the choice: Terry Beige or Dolce 51, requires Luxe trim level

OUTSIDE PROTECTIONS

- · Sprayhood with LED lighting, Strataglass windows, Charcoal Grey
- Bimini Charcoal Grey (sprayhood option required)
- Bimini for helm stations, Charcoal Grey
- Sunshade for the cockpit, Charcoal Grey (compatible with all booms)
- Sunshade on foredeck, Charcoal Grey

General Equipment list - Europe

INTERIOR EQUIPMENT

LAYOUT VERSIONS

- · 3 cabins 2 heads version
- 3 cabins 3 heads version
- Skipper cabin replacing the sail locker of the foredeck: Access through T70 deck hatch, Stainless steel ladder, 1 Berth, Toilet, Washbasin, Shower, 1 dual USB port

AMBIANCE

- Interior woodwork: Alpi oak 3 gloss + Alpikord oak floorings
- Interior upholstery according to colour chart: Fabrics, Leather, Nubuck, Ultraleather

MULTIMEDIA

- TV pre-assembly on lifting system, in the saloon
- TV pre-assembly, in the forward cabin (on bulkhead)
- Hifi APOLLO + Bose 2.1 speakers, in the saloon (in lieu of standard)

DOMESTIC APPLIANCES

- Dishwasher for 6 sets (230V)
- Built-in 22 L grill and microwave combined oven (230V)
- Wine cellar 19 bottles (230V)
- 36 L cool box with access from the galley work top, stainless steel tank (temperature adjustable from +10 °C to -12 °C)
- 2 Stainless steel fridge drawers (2 x 95L / 25 US Gal 12-24V / 230V) in lieu of standard (3 cabins 2 heads version)

ON BOARD COMFORT EQUIPMENT

- Spring mattress in the aft cabins (thickness: 160mm / 6")
- Generator (7,5 KVA, 230V, 50Hz)
- Watermaker (60 l/h / 16 US Gal/h)
- Air conditioning 44 000 BTU (+ Shore socket extension cord 15m / 49'3'') - 32A
- Forced air heating fuel
- Safe, in the forward cabin
- 12V / 230V inverter 2 000 VA
- Electric battery switch (connected to the Ship Control, controls powering on or shut-off of batteries remotely)
- 4 Lithium batteries (90 Amps) to replace the AGM batteries Weight saving: Approximately 170 kg / 375 lbs (requires Confort trim level) The lithium batteries can be used in exactly the same way as the greater number of AGM batteries that they replace. This technology allows 100% of the battery capacity to be used compared with 75% for the AGM batteries. The engine battery is still AGM.
- Seawater electric pump, in galley
- · Lee cloth (Aft cabins & Saloon sofa)