MARINE ENTERTAINMENT SYSTEM

WITH BLUETOOTH & NMEA 2000



CODE:

MS-RA70N

AUDIO SOURCES

AM / FM / USB / Bluetooth / iPod / iPhone / MTP / DAB+ Ready







KEY FEATURES

BLUETOOTH® WIRELESS TECHNOLOGY

Stream music from any device that supports A2DP Bluetooth Wireless Technology to the MS-RA70N. Artist, track and album information will be displayed on screen, with control from the stereo, remote, Fusion-Link enabled MFD or device via the Fusion-Link app.

APPLE IOS AND ANDROID/WINDOWS MEDIA PLAYBACK

Connect any compatible Apple device supporting the Apple iAP2 Lightning Connector, any supported Android AOA device via USB, or use the Fusion-Link app to control music playback through the MS-RA70N.

Audio control is limited to play, pause and skip functions from both the stereo interface and the Fusion-Link app via Bluetooth Wireless Technology. Please check device compatibility; only iAP2/Lightning™ devices are compatible with the MS-RA70N.

Note: The Fusion-Link app is available for free download from the Apple App Store® and Google Play $^{\text{TM}}$.

IPX7 WATER RESISTANT

When installed correctly, the MS-RA70N has been specifically engineered to withstand the harsh marine environment with an impressive IPX7 rating.

OPTICALLY BONDED LCD DISPLAY

The LCD display has been optically bonded to improve durability and eliminate condensation or fogging when out on the water. This screen is also optimized for daylight viewing.

FUSION-LINK CONTROL (WIRED & WIRELESS)

The Fusion-Link remote control app gives you the flexibility to control your onboard entertainment from anywhere on the boat, with multiple connectivity options available.


Connection options:

- NMEA 2000 network via a partnered Multi-Function Display.
- NRX Series remote via a stand-alone **Fusion Remote Control Network**.
- Bluetooth Wireless Technology via a compatible Apple or Android devices.
- ANT via a compatible Garmin watch with the FUSION-Link Lite app.

Note: The wireless Fusion-Link app is available for free download for any compatible smartphone or device from

the Apple App Store® or Google Play™. Fusion-Link Lite is available from the Garmin Connect IQ Store.

MULTI-ZONE TECHNOLOGY



Note: Subwoofer and full range line outs require additional amplification.

FUSION PRODUCT INFO		
CODE	GARMIN PN	EAN-13 BARCODE
MS-RA70N	010-01516-11	0753759149840
GIFT BOX DIMEN	NSIONS	
(W) 235mm [9-1/4"] (H) 95mm [3-3/4"]	(D) 175mm [6-7/8"]

KEY FEATURES

FLAT OR FLUSH MOUNTING OPTIONS

Two installation options are available for your MS-RA70N. Either install your stereo with a conventional flush mount finish, or integrate it into a glass helm with a flat surface finish, allowing for a more streamlined dash and high end aesthetics.

SIDE-FIN VCT™ COOLING

Amplifier components are integrated into the heat sink design to provide enhanced thermal transfer. FUSION Vertical Convection Technology (VCT) is designed for optimal circulation of air across the heat sink fins providing improved efficiency, maximum heat dissipation and product longevity.

DIN SIZED FORM FACTOR

The MS-RA70N has been engineered to seamlessly replace any standard DIN sized stereo, giving you a Fusion marine stereo option instead. Its low profile design allows for easy integration without the need to redesign the dash space for a Fusion stereo.

DAB+ READY

Simply connect the optional MS-DAB100A FUSION DAB+ Module with active antenna (sold separately) to the MS-RA70N to experience high quality digital radio with on-screen station information. This DAB+ module is also IPX7 water resistant and includes both pole mount and surface mount options for the antenna.

Note: Only available in regions that support DAB+.

Display	Display Size & Type	128x64 monochrome optically bonded LCD display
General	Sources	$AM \ / \ FM \ / \ USB \ / \ Bluetooth \ / \ iPod \ / \ iPhone \ / \ MTP \ / \ DAB+ \ Ready$
	FUSION-Link Control (Wired & Wireless)	Yes
	Audio Zones	2
	Amplifier	Class-AB
	Certified NMEA 2000	Yes
	Ingress Protection Rating (IPX)	IPX7
	Operating Voltage	+10.8 - 16 VDC
	Fuse Rating	15A
Power Output	Peak Power	200W (50W x 4)
	Pre-Output Voltage	4V (peak - peak)
nguages	Multiple Languages Available	English, French, German, Spanish, Dutch, Italian
Zone Connections	Line Out	1 (requires external amplification)
	Sub Out	1 (requires external amplification)
dates	Software Updates	Via USB

DIMENSIONS

