

# ANTISKID POWDER CF

## TECHNICAL DATA SHEET

### Product description

This antiskid product is resistant to abrasion and its specific gravity is low. It is made up of hollow spheres. It can be mixed with any type of mono or two component topcoat or varnish.

### Product information

Finish	Powder	
Colour	Grey .714	
Solids (by volume)	ASTM D2369	100%
Specific gravity	UNI EN ISO 2811-1	2,6 ± 0,2 g/cm <sup>3</sup>
Packaging	0,125 Lt	

### Application and use

#### SURFACE PREPARATION

It depends on the applied kind of topcoat. The addition of the ANTISKID additive does not alter characteristics and usage of the product it has been mixed with. During application, it is advisable to mix the product containing the ANTISKID additive periodically in order for the antiskid effect to have an excellent uniformity.

#### Application data

Physical characteristics	Cave inorganic subtle powder. High fluidity and easy to mix. High resistance to temperature and humidity.
Mixing ratio	50 gr per each litre of varnish or topcoat.

# ANTISKID POWDER CF

## TECHNICAL DATA SHEET

### Storage

---

It is recommended to avoid exposure to air and extreme temperatures. To maximize the shelf life in the can, it is worth checking that the container is well closed during the storage and the temperature is between 10° C and 35° C. Avoid exposure to direct sunlight.

### Safety rules

---

Observe the provisions of DPR 303 and 547. Avoid contact with the skin, for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application, use appropriate protections (masks, gloves, glasses, etc.). Before using, read sections 7-8 of the SDS.

#### INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by taking them to a recycling centre.

Packages containing the unused products: Dispose of the unused product in accordance with the law of disposal of such waste, for example by taking it to a recycling center, recycling of packaging is prohibited in this case. Do not empty into drains or watercourses. Product packaging must be kept indoor, and the temperature in the storage place must be between 10° C and 35 °C. Do not expose to sunlight.

### Notes

---

The values indicated in the present technical sheet can have slight variations from one batch to another. The applied product must not come in contact with water, chemicals or be subjected to mechanical stress before the curing is complete. Wet film thicknesses refer to a product that has not been diluted. With dilution, this value will rise. The above information is the result of accurate laboratory tests and practical experience; however, since the product is predominantly used outside the manufacturer's control. Boero Bartolomeo S.p.A can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or further information, it is recommended to contact Boero Bartolomeo S.p.A directly. The present datasheet annuls and replaces every other precedent to this one.