

# DILUENTE 6780

## TECHNICAL DATA SHEET

### Product description

Thinners are volatile liquids used to dissolve paint components, reduce viscosity and enhance the product application. The proper thinner evaporation allows the correct drying of the paint promoting the formation of an homogeneous film. Therefore, the correct use of a thinner is very important to obtain a homogeneous film.

Thinner 6780 is recommended for Gel Gloss Pro, Polyrex Pro, Wood Gloss dilution; only to clean tools used during Adherglass and Fibrodur application.

### Product information

Finish	Liquid	
Colour	Colourless .000	
Specific gravity	UNI EN ISO 2811-1	0,90 ÷ 0,95 g/cm <sup>3</sup>
Flash point	UNI EN ISO 13736	1 °C
VOC (average calculated content)	ISO 11890-2/2006	930 g/l
Packaging	0,50 – 2,50 Lt	

### Storage

It is recommended to avoid exposure to air and extreme temperatures. To maximize the shelf life in the can, it is worth checking that the container is well closed during the storage and the temperature is between 10° C and 35° C. Avoid exposure to direct sunlight.

# DILUENTE 6780

## TECHNICAL DATA SHEET

### Safety rules

---

Observe the provisions of DPR 303 and 547. Avoid contact with the skin, for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During application, use appropriate protections (masks, gloves, glasses, etc.). Before using, read sections 7-8 of the SDS.

#### INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by taking them to the recycling centre.

Packages containing the unused products: Dispose of the unused products in accordance with the law of disposal of such waste, for example by taking it to a recycling centre, recycling of packaging is prohibited in this case. Do not empty into drains or watercourses. Product packaging must be kept indoor, and the temperature in the storage place must be between 10° C and 35° C. Do not expose to sunlight.

### Notes

---

The values indicated in the present technical sheet have slight variations from one batch to another. The applied product must not come in contact with water, chemicals or be subjected to mechanical stress before the curing is complete. Wet film thicknesses refer to the product which has not been diluted. With dilution, this value will rise. The above information is the result of accurate laboratory tests and practical experience; however, since the product is predominantly used outside the manufacturer's control, Boero Bartolomeo S.p.A can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or further information, it is recommended to contact Boero Bartolomeo S.p.A directly. The present datasheet annuls and replaces every other precedent to this one.